Training Verifiers to Solve Math Word Problems

Karl Cobbe^{*} V Heewoo Jun Jacob Hilton F

Vineet Kosaraju^{*} Lukasz Kaiser Reiichiro Nakano Mohammad Bavarian Matthias Plappert Christopher Hesse Mark Chen

Jerry Tworek

John Schulman

OpenAI

Abstract

State-of-the-art language models can match human performance on many tasks, but they still struggle to robustly perform multi-step mathematical reasoning. To diagnose the failures of current models and support research, we introduce GSM8K, a dataset of 8.5K high quality linguistically diverse grade school math word problems. We find that even the largest transformer models fail to achieve high test performance, despite the conceptual simplicity of this problem distribution. To increase performance, we propose training verifiers to judge the correctness of model completions. At test time, we generate many candidate solutions and select the one ranked highest by the verifier. We demonstrate that verification significantly improves performance on GSM8K, and we provide strong empirical evidence that verification scales more effectively with increased data than a finetuning baseline.

1 Introduction

In recent years, large language models have demonstrated impressive skills across many diverse tasks (Wang et al., 2019; Brown et al., 2020). Kaplan et al. (2020) describe the consistent benefits of increasing model size, characterizing scaling trends that hold across many orders of magnitude. However, even the largest models falter when required to perform multi-step mathematical reasoning (Hendrycks et al., 2021). Model samples frequently contain catastrophic mistakes, even after the model has been appropriately finetuned. Mathematical reasoning thus reveals a critical weakness in modern language models.

One significant challenge in mathematical reasoning is the high sensitivity to individual mistakes (Shen et al., 2021a). When generating a solution, autoregressive models have no mechanism to correct their own errors. Solutions that veer off-course quickly become unrecoverable. If we rely purely on generative methods and extrapolate from current trends, we will require an exorbitant

^{*}Equal contribution. Correspondence to: Karl Cobbe <karl@openai.com>, Vineet Kosaraju <vineet@openai.com>




Figure 1: Three example problems from GSM8K. Calculation annotations are highlighted in red.

parameter count to achieve even moderate performance on distributions as challenging as the MATH dataset (Hendrycks et al., 2021). This evidence strongly motivates the search for methods with more favorable scaling laws.

We propose training verifiers to evaluate the correctness of model generated solutions, similar to concurrent work by Shen et al. (2021a). At test time, we sample a fixed number of candidate solutions and select the solution ranked highest by the verifier. Verifiers benefit both from their inherent optionality and from verification being a simpler task than generation in general.

To facilitate research, we are releasing GSM8K, a dataset of 8.5K high quality problems at the grade school math level. We designed this dataset to have high linguistic diversity while relying on relatively simple grade school math concepts. State-of-the-art language models struggle to achieve high performance on this dataset, primarily due to the high diversity among problems. At the same time, GSM8K solutions depend only on elementary concepts, so achieving high test performance is a tractable goal.

Our main contributions are as follows:

- 1. We present a curated dataset of 8.5K grade school math questions and natural language solutions, useful for probing the informal reasoning ability of large language models.
- 2. We show that, compared to a finetuning baseline, the use of verifiers results in approximately the same performance boost as a 30x model size increase, and that verifiers scale significantly better with increased data.
- 3. We show that dropout acts as a strong regularizer, significantly improving performance for both finetuning and verification.

2 Dataset

GSM8K consists of 8.5K high quality grade school math problems created by human problem writers. We segmented these into 7.5K training problems and 1K test problems. These problems take between 2 and 8 steps to solve, and solutions primarily involve performing a sequence of elementary calculations using basic arithmetic operations $(+ - \times \div)$ to reach the final answer. A bright middle school student should be able to solve every problem.

We created GSM8K based on the following design principles.

- **High Quality** We avoid error-prone scraping procedures and instead rely on human workers to create problems. After performing extensive quality control based on workers' answer agreement, we estimate that less than 2 percent of problems contain breaking errors.
- **High Diversity** We strive for high diversity among problems. We actively avoid designing problems that are drawn from the same linguistic template or differ only in superficial details, an issue that is prevalent among many other datasets. By creating each individual problem to be relatively unique, held-out test performance becomes a far more relevant metric.
- Moderate Difficulty We choose a problem distribution that is challenging for large state-of-the-art language models, without being completely intractable. GSM8K will help us better understand the data scaling trends of different models and methods in this difficulty sweet spot. Problems require no concepts beyond the level of early Algebra, and the vast majority of problems can be solved without explicitly defining a variable.
- Natural Language Solutions We collect solutions in natural language rather than as pure math expressions. We believe this is the most generally useful data format, and we expect it to shed light on the properties of large language models' internal monologues. We instructed problem writers to explain their work as much as possible, but we allowed them to write solutions in their own diverse linguistic styles.

The full GSM8K dataset can be found at https://github.com/openai/gradeschool-math. Example problems are shown in Figure 1, and we discuss additional dataset details in Appendix A.

3 Related Work

3.1 Related Datasets

Early math word problem datasets (Kushman et al., 2014; Roy and Roth, 2015) are relatively small and are not well suited for testing the limits of modern language models. Dolphin18K (Huang et al., 2016) is a larger dataset containing

18K problems, but solutions are provided only in the form of equations or final answers. AQuA-RAT (Ling et al., 2017) contains 100K problems, but this dataset unfortunately suffers from both a high degree of problem templatization and poor quality control of the natural language solutions. MathQA is a recently released subset of AQuA-RAT focused on correcting these mistakes (Amini et al., 2019), but even the corrected dataset has data quality issues, with around 30% of the data having inconsistencies (Miao et al., 2021). Ape210K (Zhao et al., 2020) is the largest publicly available dataset, consisting of 210K Chinese elementary school-level math problems. However, due to the language barrier and the lack of natural language solutions, we're unable to evaluate our methods on this dataset.

The recently developed ASDiv dataset (Miao et al., 2021), which contains 2.3K math word problems, addresses common flaws in prior datasets by ensuring problems have both high diversity and high quality. We share those design principles in the creation of GSM8K. However, we note that GSM8K is larger, provides natural language solutions, and consists of problems that on average require more steps to solve. The MATH dataset (Hendrycks et al., 2021) is larger and significantly more complex than GSM8K, but the high difficulty makes it challenging to accurately measure progress given the current capabilities of state-of-the-art language models.

Other recent reasoning-related datasets have focused on mathematical reasoning on symbolic math (Lample and Charton, 2019), reading comprehension (LogiQA) (Liu et al., 2020), and commonsense question answering (CommonsenseQA) (Talmor et al., 2018). Similar to CommonsenseQA, GSM8K includes questions that require basic background knowledge, like the number of days in a week. Similar to LogiQA, which requires a mix of reading comprehension and logical reasoning, GSM8K's main difficulty lies in both properly interpreting a question and reasoning through the steps to solve it.

3.2 Related Methods

Previous work has attempted to solve classic math word problem benchmarks with recurrent seq2seq models (Sutskever et al., 2014) and closely related variants (Wang et al., 2017; Huang et al., 2018). More recent work has improved performance by designing specialized encoder-decoder architectures (Amini et al., 2019; Chiang and Chen, 2018; Xie and Sun, 2019; Chen et al., 2020; Li et al., 2020), with the strongest results often relying on large pretrained encoders from the BERT family (Chen et al., 2019; Kim et al., 2020; Liang et al., 2021).

Other recent work has recommended additional pretraining tasks to further improve the math reasoning skills of large transformer-based models. Hendrycks et al. (2021) propose pretraining models on a new AMPS corpus, derived from Khan Academy problems and Mathematica scripts. Similarly, Shen et al. (2021b) propose a pretrained a corpus of pre-K to college level curricula extracted from the internet, and Peng et al. (2021) propose pretraining by predicting masked subexpressions from expression trees.

Similar to verification, other methods have finetuned a language model to




Figure 2: Final test performance for various GPT-3 model sizes after finetuning on training sets of different sizes. Mean and standard deviation is shown across 3 runs.

select among many model completions. Nichols et al. (2020) proposed a sampleand-rank approach to improve the collaborative storytelling ability of large language models, with the training signal coming from the preferences of human workers. In concurrent work closely related to our own, Shen et al. (2021a) applied a similar approach to solving math word problems, jointly training a model to both generate and rank solutions. Our work shares many fundamental similarities with their approach, though we differ in several key respects. First, we focus attention on the space of natural language solutions, as this is a richer and more general solution format than pure mathematical expressions. Moreover, this choice enables our models to develop verbal analytical skills and to produce solutions that are more readily interpretable by humans. Second, we provide evidence that verifiers scale far more favorably with additional data than baseline methods. Finally, we use separate generator and verifier networks, in order to prevent the generator from overfitting.

4 Methods

We investigate two methods to solve problems in GSM8K: finetuning and verification. Finetuning, our baseline method, uses the same language modeling objective as the generative pretraining in GPT-3 (Brown et al., 2020). At test time, we judge performance by autoregressively sampling a single low temperature solution and checking whether the final answer is correct. In contrast, verification consists of sampling multiple high temperature solutions, assigning each solution a score, and outputting the highest ranked solution. Verifiers are trained to judge the correctness of solutions, with the training signal determined solely by whether or not the solution reached the correct final answer.




Figure 3: Test solve rate after finetuning a 6B model on the full GSM8K training set, when the model is allowed to make 1 guess (left) or 100 guesses (right).

For both methods, we use models from the GPT-3 family as our initialization, primarily focusing on the 175B and 6B model sizes. The 175B model is the largest and produces the most impressive results, while the 6B model is significantly more convenient for research purposes. We discuss hyperparameter choices in Appendix B.

Our models frequently fail to accurately perform calculations. Although larger models make fewer arithmetic mistakes than smaller models, this remains a common source of errors. To mitigate this issue, we train all models to use a calculator by injecting calculation annotations into the training set. At test time, a calculator will override sampling when the model chooses to use these annotations. Details can be found in Appendix C.

4.1 Finetuning

We perform finetuning by updating model parameters to minimize the crossentropy loss over all training tokens. Figure 2 shows test performance after finetuning on training sets of varying sizes for 20 epochs. We visualize the same data both as a function of training set size and as a function of model size. Test performance is determined by a single low temperature (T = 0) sample for each test problem. Unsurprisingly, we see that the 175B model significantly outperforms the smaller models. Assuming a log-linear trend, we can naively extrapolate these results to estimate that a model with 10^{16} parameters would be required to reach an 80% solve rate, when using the full GSM8K training set. It is even harder to extrapolate along the data dimension, since performance does not appear to follow a log-linear trend. Nevertheless, it appears likely that the 175B model would require at least two additional orders of magnitude of training data to reach an 80% solve rate.

In Figure 3, we show how 6B test performance varies over the course of 100




Figure 4: A diagram of the verification training pipeline.

training epochs. We use test@N to denote the percentage of problems solved correctly at least once when allowing the model to make N separate guesses for each problem. We use a low temperature (T = 0) to generate test@1 samples and we use a higher temperature (T = 0.7) to generate test@100 samples. Both temperature values were chosen empirically to produce the best results. Test@1 performance improves approximately monotonically, even though we quickly begin overfitting on test loss. Unfortunately, test@100 performance degrades much more sharply than test@1 as we increase the number of epochs. This is to be expected: as the model repeatedly encounters the same data, it becomes increasingly uncalibrated and overconfident in its predictions. At test time, this overconfidence leads to poor coverage of the solution space, an effect which only becomes noticeable when we are considering multiple samples at test time.

Choosing a model with good coverage is critical to successfully train verifiers. Empirically, we see that test@100 performance peaks within the first few epochs. For this reason, we use models trained for 2 epochs to generate samples for training verifiers. We provide several example solutions from 6B and 175B models in Appendix D. We also note that it is important to allow the model to generate the full natural language solution before outputting a final answer. If we instead finetune a 6B model to directly output the final answer without any intermediate steps, performance drops drastically from 20.6% to 5.2%.

4.2 Verification

To improve upon the finetuning baseline, we train verifiers to judge the correctness of model-generated solutions and search against these verifiers at test time. Conditioned on the problem and a candidate solution, the verifier outputs the probability that the solution is correct. Training solutions are labeled as correct or incorrect based solely on whether they reach the correct final answer. In practice, some solutions will reach the correct final answer using flawed reasoning, leading to false positives.





Figure 5: A comparison between finetuning and verification using 6B and 175B model sizes. Verification considers 100 solutions per problem. Mean and standard deviation is shown across 3 runs, except for 175B verification which shows only a single run.

As shown in Figure 4, we train the verifier as follows:

- 1. Finetune a model (the "generator") for 2 epochs on the training set.
- 2. Sample 100 completions from the generator for each training problem and label each solution as correct or incorrect.
- 3. Train a verifier for a single epoch on this dataset.

Training for 2 epochs is enough for the generator to learn basic skills in this domain. We choose not to train for longer, since the diversity of generated solutions begins to collapse after this point, as shown in Figure 3. We train separate generator and verifier models to limit the generator's training and prevent overfitting, but in principle, it should be possible to combine these models. Unless otherwise specified, we use the same model size for the generator and the verifier. In addition to predicting solution correctness, we also train the verifier with the same language modeling objective as the generator. This serves as a valuable auxiliary objective for the verifier. We discuss additional verifier training details in Appendix E.

At test time, we sample 100 completions to each test problem, rank them with the verifier, and then return the one with the highest verifier score. A comparison between verification and finetuning is shown in Figure 5 for both the 6B and 175B model sizes. We find that it is not beneficial to use verification at low dataset sizes. We believe this is due to the pressure to overfit to the correct answer: with small datasets, overfitting to the correct answer happens faster than learning more generalizable properties of correct reasoning. However, once we use a sufficiently large dataset, we see a strong boost from verifiers.



correctness after every to- to predict correctness and ken (token-level) and one perform language modeltrained to predict correct- ing (joint) and one trained ken (solution-level)

(a) Comparison between a (b) Comparison between (c) Performance when vary-(verification-only)

verifier trained to predict a verifier trained jointly ing the size of the generator and the verifier in isolation. Increasing the size of the generator has a larger ness after only the final to- only to predict correctness impact than increasing the size of the verifier.

Figure 6: Verification ablations


It's interesting to note that the 175B verifiers "take off" earlier than the 6B verifiers, requiring fewer training problems to surpass the finetuning baseline. See Appendix D for example solutions found by verifiers and Appendix F for a visualization of verifier confidence.

4.3Verification Ablations

We can either train verifiers to make a single scalar prediction conditioned on the entire generated solution, or to make a scalar prediction after each token in the solution. By default, we choose the latter, training verifiers to make predictions after each token. This can be viewed as a token-level value function. We compare these two methods in Figure 6a, respectively labeled "solutionlevel" and "token-level".

Predicting the value function at every token is a more challenging and noisier task than judging only the full completion. However, despite the initially slower training, the token-level verifier ultimately outperforms the solution-level verifier. Moreover, the token-level verifier is still improving late in training, whereas the solution-level verifier quickly shows signs of overfitting. We hypothesize that the full value function provides a useful auxiliary signal that encourages the model to judge the reasoning throughout solutions, rather than merely memorizing the correct final answer.

In Figure 6b, we ablate the objective used when training verifiers. As discussed in Section 4.2, we can optionally include a language modeling objective alongside the verification objective. We compare using both objectives to using only the verification objective. Although both are reasonable choices, including the language modeling objective is a strict improvement. This makes intuitive



(a) 6B verification test performance when given varying numbers of completions per problem to rank.

(b) 6B verification test performance when varying the number of top ranked samples allowed to vote on the answer.

Figure 7: Performance as the amount of test time compute varies.

sense: better understanding this language distribution should only aid the verifier in discriminating between samples.

In Figure 6c, we separately ablate the model size of the generator and the verifier. We find that using a large generator with a small verifier performs significantly better than using a small generator with a large verifier. Verification is still remarkably effective, even when the verifier is much smaller than the generator. This suggests that the verifier may often be relying on relatively coarse heuristics to discriminate between solutions from a given generator, rather than attempting a more thorough form of verification.

5 Additional Experiments

5.1 Test Time Compute

At test time, we can choose to generate arbitrarily many solutions to be judged by the verifier before selecting the highest ranked completion. Figure 7a shows how 6B verifier performance varies with the number of completions per test problem. At this scale, performance improves as we increase the number of completions up to 400. Beyond this point, performance start to decrease. This suggests that the benefits of search are eventually outweighed by the risk of finding adversarial solutions that fool the verifier. In general, we evaluate verifier test performance using 100 completions, since this captures most of the benefits of verification with a relatively modest compute cost.

To further increase performance, we can take a majority vote among the top verifier-ranked solutions instead of selecting only the single top solution.




Figure 8: 6B finetuning and verification dropout ablations.

This voting process considers only the final answer reached by the individual solutions: the final answer selected is the one with the most votes. Figure 7b shows how performance varies as we allow a greater number of top samples to cast a vote. Unsurprisingly, when starting with a greater number of samples, we can afford to allow a greater number of samples to cast a vote. When we have only 100 samples, it is optimal to allow only the top 3-5 samples to cast a vote. When we have 3200 samples, it is approximately optimal to allow the top 30 to cast a vote.

5.2 Regularization

We find that both finetuning and verification strongly benefit from the use of dropout as a regularizer. Specifically, we apply residual dropout (Vaswani et al., 2017) along the residual paths of each layer in the network. We use 20% dropout for all dropout experiments, chosen based on the results of a hyperparameters sweep. We note that GPT-3 models are not pretrained with dropout. For experiments involving dropout, we therefore perform additional pretraining with dropout before subsequently finetuning the models. This mitigates the distribution shift the model experiences during finetuning.

We first investigate the effect of dropout on finetuning across various training set sizes. Figure 8a shows that dropout leads to a significant improvement over baseline. We next investigate the effect of dropout on verifiers, considering both the solution-level and token-level variants. In Figure 8b, we see that dropout significantly improves solution-level verifiers, mitigating the overfitting that occurs in the unregularized baseline. Notably, using dropout with solutionlevel verifiers reaches a similar level of performance as token-level verifiers. In Figure 8c, we apply dropout to token-level verifiers. Since token-level verifiers are already less susceptible to overfitting, it is no surprise that the impact of dropout is less significant. Nevertheless, we do still see a slight gain from training token-level verifiers with dropout. Note that we increase the batch size for token-level verifiers by a factor of 4, to better handle the more difficult objective and the noise from dropout.

6 Conclusion

We have seen that verification provides a significant performance boost relative to a finetuning baseline. On the full dataset, 6B verification slightly outperforms a finetuned 175B model, thereby offering a boost approximately equivalent to a 30x model size increase. We have also seen that token-level verifiers are less prone to overfitting than solution-level verifiers, and that all methods benefit from regularization with residual dropout. We expect verification to scale well to problem distributions that require more complex mathematical reasoning, and we hope GSM8K supports the development of new methods that scale even better.

Acknowledgements

We thank Dan Hendrycks, Leo Gao, Alec Radford, and Giambattista Parascandolo for their valuable feedback on this paper; Harri Edwards, Yura Burda, Michael Wu, and Nick Ryder for many insightful conversations; Michael Petrov, Alethea Power, and Jacob Jackson for their technical assistance; the OpenAI Supercomputing team for the infrastructure that made these experiments possible; and the team at Surge AI for performing the GSM8K data collection.

References

- A. Amini, S. Gabriel, P. Lin, R. Koncel-Kedziorski, Y. Choi, and H. Hajishirzi. Mathqa: Towards interpretable math word problem solving with operationbased formalisms. arXiv preprint arXiv:1905.13319, 2019.
- T. B. Brown, B. Mann, N. Ryder, M. Subbiah, J. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. arXiv preprint arXiv:2005.14165, 2020.
- K. Chen, Q. Huang, H. Palangi, P. Smolensky, K. D. Forbus, and J. Gao. Mapping natural-language problems to formal-language solutions using structured neural representations. In *ICML*, 2020.
- X. Chen, C. Liang, A. W. Yu, D. Zhou, D. Song, and Q. V. Le. Neural symbolic reader: Scalable integration of distributed and symbolic representations for reading comprehension. In *International Conference on Learning Representations*, 2019.
- T.-R. Chiang and Y.-N. Chen. Semantically-aligned equation generation for solving and reasoning math word problems. arXiv preprint arXiv:1811.00720, 2018.
- D. Hendrycks, C. Burns, S. Kadavath, A. Arora, S. Basart, E. Tang, D. Song, and J. Steinhardt. Measuring mathematical problem solving with the math dataset. arXiv preprint arXiv:2103.03874, 2021.

- D. Huang, S. Shi, C.-Y. Lin, J. Yin, and W.-Y. Ma. How well do computers solve math word problems? large-scale dataset construction and evaluation. In Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 887–896, 2016.
- D. Huang, J. Liu, C.-Y. Lin, and J. Yin. Neural math word problem solver with reinforcement learning. In *Proceedings of the 27th International Conference* on Computational Linguistics, pages 213–223, 2018.
- J. Kaplan, S. McCandlish, T. Henighan, T. B. Brown, B. Chess, R. Child, S. Gray, A. Radford, J. Wu, and D. Amodei. Scaling laws for neural language models. arXiv preprint arXiv:2001.08361, 2020.
- B. Kim, K. S. Ki, D. Lee, and G. Gweon. Point to the expression: Solving algebraic word problems using the expression-pointer transformer model. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 3768–3779, 2020.
- N. Kushman, Y. Artzi, L. Zettlemoyer, and R. Barzilay. Learning to automatically solve algebra word problems. In *Proceedings of the 52nd Annual Meeting* of the Association for Computational Linguistics (Volume 1: Long Papers), pages 271–281, 2014.
- G. Lample and F. Charton. Deep learning for symbolic mathematics. arXiv preprint arXiv:1912.01412, 2019.
- S. Li, L. Wu, S. Feng, F. Xu, F. Xu, and S. Zhong. Graph-to-tree neural networks for learning structured input-output translation with applications to semantic parsing and math word problem. *EMNLP*, 2020.
- Z. Liang, J. Zhang, J. Shao, and X. Zhang. Mwp-bert: A strong baseline for math word problems, 07 2021.
- W. Ling, D. Yogatama, C. Dyer, and P. Blunsom. Program induction by rationale generation: Learning to solve and explain algebraic word problems. *arXiv preprint arXiv:1705.04146*, 2017.
- J. Liu, L. Cui, H. Liu, D. Huang, Y. Wang, and Y. Zhang. Logiqa: A challenge dataset for machine reading comprehension with logical reasoning. In *IJCAI*, 2020.
- S.-Y. Miao, C.-C. Liang, and K.-Y. Su. A diverse corpus for evaluating and developing english math word problem solvers. arXiv preprint arXiv:2106.15772, 2021.
- E. Nichols, L. Gao, and R. Gomez. Collaborative storytelling with large-scale neural language models. arXiv preprint arXiv:2011.10208, 2020.
- S. Peng, K. Yuan, L. Gao, and Z. Tang. Mathbert: A pre-trained model for mathematical formula understanding. ArXiv, abs/2105.00377, 2021.

- S. Roy and D. Roth. Solving general arithmetic word problems. In Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing, pages 1743–1752, Lisbon, Portugal, Sept. 2015. Association for Computational Linguistics. doi: 10.18653/v1/D15-1202. URL https://aclanthology.org/D15-1202.
- J. Shen, Y. Yin, L. Li, L. Shang, X. Jiang, M. Zhang, and Q. Liu. Generate & rank: A multi-task framework for math word problems. *arXiv preprint* arXiv:2109.03034, 2021a.
- J. T. Shen, M. Yamashita, E. Prihar, N. Heffernan, X. Wu, B. Graff, and D. Lee. Mathbert: A pre-trained language model for general nlp tasks in mathematics education, 08 2021b.
- I. Sutskever, O. Vinyals, and Q. V. Le. Sequence to sequence learning with neural networks. In Advances in neural information processing systems, pages 3104–3112, 2014.
- A. Talmor, J. Herzig, N. Lourie, and J. Berant. Commonsenseqa: A question answering challenge targeting commonsense knowledge. arXiv preprint arXiv:1811.00937, 2018.
- A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin. Attention is all you need. In Advances in neural information processing systems, pages 5998–6008, 2017.
- A. Wang, Y. Pruksachatkun, N. Nangia, A. Singh, J. Michael, F. Hill, O. Levy, and S. R. Bowman. Superglue: A stickier benchmark for general-purpose language understanding systems. arXiv preprint arXiv:1905.00537, 2019.
- Y. Wang, X. Liu, and S. Shi. Deep neural solver for math word problems. In Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, pages 845–854, Copenhagen, Denmark, Sept. 2017. Association for Computational Linguistics. doi: 10.18653/v1/D17-1088. URL https://aclanthology.org/D17-1088.
- Z. Xie and S. Sun. A goal-driven tree-structured neural model for math word problems. In *IJCAI*, 2019.
- W. Zhao, M. Shang, Y. Liu, L. Wang, and J. Liu. Ape210k: A largescale and template-rich dataset of math word problems. arXiv preprint arXiv:2009.11506, 2020.

A Dataset Details

We initially collected a starting set of a thousand problems and natural language solutions by hiring freelance contractors on Upwork (upwork.com). We then worked with Surge AI (surgehq.ai), an NLP data labeling platform, to scale up our data collection. After collecting the full dataset, we asked workers to re-solve all problems, with no workers re-solving problems they originally wrote. We checked whether their final answers agreed with the original solutions, and any problems that produced disagreements were either repaired or discarded. We then performed another round of agreement checks on a smaller subset of problems, finding that 1.7% of problems still produce disagreements among contractors. We estimate this to be the fraction of problems that contain breaking errors or ambiguities. It is possible that a larger percentage of problems contain subtle errors.

To assist contractors with writing questions, we provided seed questions automatically generated from a few-shot prompted 175B GPT-3 model. Contractors were allowed to use those seed questions directly, to use them as inspiration and make modifications, or to come up with their own questions entirely. We instructed contractors to be as descriptive as possible in their solutions, and to not re-use problem settings or templates between different questions. To ensure contractors were not re-using problem templates, we computed pairwise similarity scores between problems and used this to provide feedback to contractors.

B Hyperparameters

We include a table of important hyperparameters below. We performed sweeps of the learning rate and batch size by an order of magnitude in both directions from the values in the table and were unable to find any significant improvements. Other reasonable choices for both the verifier temperature (eg: 1.0 instead of 0.7) and objective (cross-entropy instead of mean squared error) also had negligible effect in our ablations.

General Hyperparameters	Value
Batch Size	3.2×10^4 tokens
Max Sample Length	400 tokens
Tokenization	reversible_50000
Optimizer	Adam, $\beta_1 = 0.9, \beta_2 = 0.95$
Dropout	0.0
Learning Rate Schedule	Linear decay to 0
Finetuning Hyperparameters	Value
Epochs	20
Sampling Temperature	0 (argmax)
Base Learning Rate (α)	$1.6 \times 10^{-5} (3B)$
	$1.2 \times 10^{-5} (6B)$
	$1.0 \times 10^{-5} (12B)$
	$6.0 \times 10^{-6} (175B)$
Learning Rate	0.1 imes lpha
Verification Hyperparameters	Value
Epochs	2 for generator, 1 for verifier
Sampling Temperature	0.7
Learning Rate	1.0×10^{-5}
Loss weight	1.0
Verifier loss	MSE
Completions per train problem	100
Completions per test problem	100

Table 1: Hyperparameters used for all experiments, unless explicitly said otherwise. Notable exceptions include Figure 8c, which uses 4x more tokens per batch and 300 completions at both training and test time. All dropout experiments in Figure 8 use 20% dropout. Figure 7a uses verifiers trained on 100 completions, but searching over more completions at test time.

C Calculator Annotations

The calculator annotations were not provided by human contractors: they were generated by a combination of hard-coded logic and a finetuned language model. The logic for auto-generating calculator annotations is imperfect. It is highly unlikely to generate any incorrect annotations, but it is not uncommon for it to ignore some lines that could be annotated.

During training, there is no special distinction between the annotated tokens and the rest of the solution: they are all just tokens. During testing, we override model sampling when a well-formatted annotation exists, specifically overwriting the token(s) directly following "=" and within <<...>>.

To simulate the calculator, we simply use the python eval function to evaluate the tokens in the expression (Figure 9). Evaluations that time out or throw an error result in the annotations being skipped and the model being sampled from as usual.

We note that the original version of our calculator, used for all results in this paper, had some minor implementation bugs. Our reported test performance is therefore a slight underestimate, though the magnitude of this discrepancy is less than 1% in most experiments. Fixing the calculator improves verification test performance by about 1% when using the full GSM8K training set.




Figure 9: A diagram of the calculator sampling procedure.

D Example Model Solutions

We showcase a handful of samples comparing finetuning and verification at both 6B and 175B scale. Samples were slightly cherry-picked for diversity.

Dean's mother gave him \$28 to go to the toy store. Dean bought 6 toy cars and 5 teddy bears. Each toy car cost \$2 and each teddy bear cost \$1. His mother then feels generous and decides to give him an extra \$10. How much money does Dean have left?	Shiela is required to submit a 15-page research paper. She already finished writing 1/3 of the paper. How many pages does she have left to write?
Ground Truth: The cost of the log cars is 6 cars $*$ \$2/car = \$<<672=12>12. The cost of the leddy beams is 5 bears $*$ \$1/baar = \$<<71=5>5. The total cost of the toys is 12 + \$6 = \$<<72=5=17>17. Adding the tow cannots of movely him other gave him, we find that Dean has \$28 + \$10 = \$<<740=10=38>>38 o spend. Dean has \$38 - \$17 = \$21 left. A: 21	Ground Truth: Shiela has already written one third of the paper which is 15 pages x 1/3 = <<15*1/3=5>>5 pages. So, the sill needs to write 15 pages - 5 pages = <<15.5=10>>10 pages. A: 10
	68 Finetuning: [correct] She has written 1/3 * 15 pages = <<1/3*15=5.0>>5 pages. The rest of the paper is 15 pages - 5 pages = <<15-5=10.0>>10 pages. A: 10
$\begin{array}{l} \textbf{68 Finaturalistic [Incorrect]}\\ \textbf{11 focould fibe uprais (s \times S2 = S<<0?)=1/2.\\ The cost of the toxicly beams is 5 \times S1 = S<<0?1=2.\\ The toxicl cost of the toxy is 15 2 + S5 = S<1245=17>>17.\\ Dean has 528 - 517 = S<28.47=11>>11 left.\\ A: 11 \end{array}$	68 Verification: [correct] Shiele has writen 1/3 x 15 = <<13*15=5.0 > ages. So, the has 15 - 5 = <<15.5 = 10.0 > 10.0 pages left to write. A: 10
B Verification: [incorrect] The cost of the toys for Dean was 6 × \$2 = \$<<672=12>>12. The cost of the toys for Dean was 6 × \$2 = \$<<671=50>5. The total cost of the toys for bin finding \$1 = \$\$ = \$\$<=5<71=50>5. The total cost of the toys for bin finding \$12 = \$\$ = \$\$ = \$<<271>7. Dean's mother gives limit an extra \$10, which makes the total amount of money he has left \$28 - \$17 = \$<<281>71. X. 11	1758 Finetuning: [correct] Shela has withen 13 x 15 = <<13*15=5.0>>5 pages. Therefore, she has 15 - 5 = <<15-5=10>>10 pages left to write. A: 10
	175B Verification: [correct] Shiele has finished writing $1/3 \times 15 = <<1/3^{+}15=5,0>5$ pages. Thus, she has $15 - 5 = <<15-5=10,0>>10$ pages left to write. A: 10
$ \begin{array}{l} \textbf{173B Instauring: [correct]} \\ The cost of the locar is is 4 × 32 = 45<-672-12>-12. \\ The cost of the locardy beams is 5 × 51 = 54<-51*50>-5. \\ The local cost of the locar is 32 + 53 = 54<-724*51*2>71. \\ The locard locar of the locar is 32 + 53 = 54<-724*51*2>71. \\ The locard locar of locar is 32 + 53<-724 + 10>+11. \\ The locard locar is 32 + 53<-724 + 10>+11. \\ The locard locar is 32 + 53<-724 + 10>+11. \\ The locard locar is 32 + 53<-724 + 10>+11. \\ The locard locar is 32 + 53<-724 + 10>+11. \\ The locard locar$	The cheese pizza is cut into 12 slices and the pepperon pizza is cut into 8 slices. If Kate's 6 friends each eat 6 cheese pizza slices and 4 pepperon pizza slices, how many pizza pies does she need to buy?
175B Verification: [correct] Deen spent 6*2 = \$<-6*2*12>12 on toy cars. Deen spent 5*1 = \$<-6*15>5 on teddy bears. He had 25*125 = \$<-6*2*12>5*11 left. His mother gave him an extra \$10 making his total 11+10 = \$<<11+10=21>>21. A : 21	Ground Truth: Kate's finends and 6 x 6 = <<676=36>>36 cheese pizza slices. Her finends and 5 x 4 = <676=3242 popperorn jizza slices. Kate needs to buy 36 1/2 = <621/2=>>3 cheese jizza pies. She needs to buy 24 / 8 = <24/8=>>3 popperorn jizza pies. She needs to buy a total of 3 + 3 = <31>3=>>6 pizza pies. A: 6
A performa company is thying to create new scents. They already have 4 vanitia scents and 8 hully scents available and they need to decide when hind of scent to focus on. They decide to focus on decide to the scents and they need to decide when hind of scent to focus on. They decide to focus on of the day, they self 5 of each of the vanitial scents and 2 of each of the fully scents available. How many more vanities contrast of the vanitial scents and 2 of each of the fully scents available. How many more vanities contrast of company with the fully scents available. How many more vanities contrast of company with the fully scents available.	68 Finaturing: [Incorrect] Kate 6 finaturing: Incorrect] This is a total of 36 slices + 6 slices = <30+8=44>>44 slices needed to buy. Therefore, Kate needs 44 slices / 12 slices/pizza = <<44/12=3.666666666666666666666666666666666666
Ground Truth: The store sold 4 types of vanilla scents * 5 sales each = <4*5>20>>20 of the vanilla scents. The store sold 8 types of fruity scents * 2 sales each = <62*2=16>>16 of the fruity scents. This means that the store sold 20 vanilla – 16 fruity = <<20-16=4>>4 more vanilla scents. A: 4	BY werlication: [Incorrect] If Kalk's 6 friends ast 6 cheese pizza silose each, then she needs 6*12 = <<6*12=72>>72 cheese pizza silosa. If Kale's 6 friends eat 6 pepperoni pizza silose each, then she needs 4*8 = <<4*8=32>>32 pepperoni pizza silosa. In total, Kate needs 72+32 = <<72+32<104>>104 pizza silose. X. 104
68 Finetuning: [incorrect] The perfume company sold 5 turnils A and 2 turnils B, so 5 + 2 = <<5+2<7>>7 Vanilla scents sold. The yeas cells 2 "Turky And 5 Fruity B, so 2 + 5 = <<2+5=7>7 Fruity scents sold. The Vanilla scents sold 7 - 5 = <<7+5=>>2 more than the Fruity scents. A : 2	175B Finetuning: [incorrect] Friends ealing cheese pizza will eal $12^{\circ}6 = <<12^{\circ}672>>72$ cheese pizza slices. Friends ealing opperoni pizza will eal $8^{\circ}4 = <38^{\circ}4-32>>32$ pepperoni pizza slices. Total alices eaten will be $72^{\circ}+32^{\circ}=<72^{\circ}+22^{\circ}=100>>104$ slices. Kate will need buy 104 112 $e^{-104/226}$ abcededededededededededededededededededed
68 Verification: [correct] There were 5 vanilla scents sold in total, so they sold 5 x 4 = <<5'4=20>>20 vanilla scents. They sold 2 fully scents in total, so they sold 2 x 8 = <<2*8=16>>16 fully scents. Therefore, the vanilla scents sold 0-16 = <<20+16/s4>>4 more than the fully scents.	Kate will need to buy 104 / $B = <<104/8=13.0>13 pepperoni pizza pies. She will need to buy 13 + 8 = <<13+8=21>>21 pizza pies. A: 21$
Therefore, the variate scenes sold 20 * 10 = <20*10-42*4 more than the noisy scenes. A: 4	175B Verification: [Incorrect] She has 6 friends who eat 12 cheese slices each so they eat 6*12 = <<6*12=72>>72 cheese slices She has 4 friends who eat 8 papperoni slices each so they eat 4*8 = <<4*8=32>>32 pepperoni slices
1758 Finaturing: [corract] They sold 5 ⁴ = «5 ⁴ /20>20) vanilla scents. They sold 2 ² = «<2 ² b=16>>16 ruly scents. They sold 20 - 16 = <20-18=4>>4 more vanilla scents. A: 4	Together her friends eat 72+32 = <72+32 = <104>>104 silces There an 12 cables alices in 1 size pixe pixe and she needs to buy 72 cheese silces so she needs 72/12 = <72/12=0.0>6 pizza pixes There are 8 perpendral silces in 1 pizza pix and she needs to buy 32 pepperoni silces so she needs 328 < <328-40.0>4 pizza pixes In total she needs to buy 6 pizza pixes pixes in to cheese and 4 pizza pixes for pepperoni so she needs to buy
1758 Verification: [correct] The pertine company sold 5 of each of the vanilla scents for a total of 5*4 = <<5*4=20>>20 vanilla scents. They also sold 2 of each of the fruity scents for a total of 2*8 = <<2*8=16>>16 fruity scents. Therefore, the pertune company sold 20-16 = <<20-16=4>>4 more vanilla scents than fruity scents. A 4	6+4 <<6+4=10>10 pizza pies A: 10
L	I contraction of the second

Cindy's math and science books weigh 2 pounds each. Her French book weighs 4 pounds and her English book weighs 3 pounds. Her history book weighs twice as much as her English book. If Cindy carries all of her books at once, what will be the total weight of the books she is carrying?	Jeff and Brad are trying to divide 100 dollars between them. Jeff gets 4 times as much as Brad. How much does Jeff get in dollars? Ground Truth:
Ground Truth: The math and science book weigh 2 pounds each so they weigh 2'2 = <<2'2=4>>4 pounds Her history books weighs twice the amount of her 3 pound English book so it weighs 2'3 = <<2'3=6>>6 pounds	Brad gets 100/5=<<100/5=20>>20 dollars. Jeff gets 20'4=<<20'4=80>>80 dollars. A: 80
When you add the weight of all of her textbooks together, they weight 4 +4+3+6 = <<4+4+3+6=17>17 pounds A: 17	6B Finetuning: [incorrect] Let x be the amount Brad gets. Jeff gets 4*x dolars. 100≖x+4*x
68 Finetuning: [correct] Cindy's math and solence books weigh? 2 pounds each for a total of 2'2 = <<2'2:=4>>4 pounds Her French book weight 4 pounds and her English book weight 3 pounds for a total of 4+3 = <<4'3:>7>> pounds Her history book weight kinds as much as her English book which weights 3 pounds so it weights 2'3 =<2'2'3:=5> pounds	100-5°x 100-5°x 20°x 100-20°x 100-100 x≪-228=25>-25 dollars A: 25
B Verification: [incorrect] The French book weighs 4 pounds and the English book weighs 3 pounds, for a total of 4 + 3 = <<44.37>7 pounds.	(B3 Worlfication: [incorrect] Since Brad gets 100 dollars, then 4 times as much Jeff gets 4*100 = <<4*100=400>>400 dollars. Therefore, Jeff gets 400 dollars. A: 400
Her history book weighs twice the weight of her English book, for a total of 2 x 3 = <<2'3=6>>6 pounds. The total weight of her books is 7 + 6 = <<7+6=13>>13 pounds. A: 13	175B Finetuning: [Incorrect] Let kbe the amount of money Brad gets. Joff gets 4* colors. 4* two=100 5* x=100
175B Finetuning: [incorrect] The total weight of Crind's main and science books is 2*2=<4?2=4>>4 pounds. The total weight of her Franch and English books is 4+3=>>7 pounds. The weight of her history book is 7?2=<7?2=11>>14 pounds. The total weight of all of her books is 4+714=<4?7+17=42>>54 pounds.	x≪<25=25>25 Jeff gels 25'4=<<25'4=100>>100 dollars. A: 100
A: 25 1758 Verification: [incorrect] Her English book weighs 3 pounds. Her history book weighs 3 x 2 << <372=0>6 pounds. So all of her books weigh 2 + 4 + 3 + 6 = <24+43+6=15>>15 pounds. A: 15	175B Verification: [correct] Let x be the amount of money that Brad gets. Jeff gets 4*x. The total is x+4*y = 100 oblans. This simplifies to 5*y = 100. So the value of x is 1005 = <<<120,D>>20 dollars. Then Jeff gets 4*x = 4*20 = <<<4*20=80>>80 dollars. A: 80
The Kennel house keeps 3 German Shepherds and 2 Buildogs. If a German Shepherd consumes 5 kilograms of dog tood and a buildog consumes 3 kilograms of dog food per day. How many kilograms of dog tood will be need in a veck?	Bob spands \$27000 distributed between 3 schools to buy books. He can buy 100 books for \$500. How many books can he buy per school?
Ground Truth: The German Shepherds consume 3 x 5 = <<3*5=15>>15 kilograms of dog food per day. The Buldogs consume 2 x 3 = <<2*3=b>-6 kilograms of dog food per day. The dogs can consume a total of 15 = 6 = <<15+6?=2*2*2 kilograms of dog food per day. Therefore, hay need 21 x 7 = <<21*7=147>>147 kilograms of dog food in a week. X 147	Ground Truth: He spends 27000/3=5<-27000/3=9000>9000 Each book coat 5000100=5<-50 So he can buy 9000/5=<5000/5=1800>>1800 books per school A: 1800
68 Finetuning: [Incorrect] The German Shepherd needs 5 x 7 = <<5'7=35>>35 kilograms of dog food per week. The Buildogs need 2 x 7 = <<2'7=14>>14 kilograms of dog food per week.	6B Finetuning: [Incorrect] He buy 2700500=<<27000500=54 (Jo>>54 books So he can buy 54/3=<<
Therefore, they need a total of 35 + 14 = <<35+14=49>>49 kilograms of dog food per week. A: 49 68 Verification: [correct]	6B Verification: [incorrect] He has \$27000 / \$500 = < 7000/500=54.0 >54 books So he can buy 54 books / 3 schools = <<54/3=18.0>>18 books per school A: 18
3 German Shepherds will consume a total of \$\$ 3\$ = <375=15>-15 kilograms of dog food per day. 2 Buildogs will consume a total of \$\$ 2\$ <<372=50-5 kilograms of dog food per day. 50, they will consume a total of \$\$ + 6 = <15+62<1>21 kilograms of dog food per day. Therefore, they will require 21 x7 = <<217=147>-147 kilograms of dog food in a week. A: 147	175B Finetuning: (incorrect) He spends 27000/500=<27000/500=54.0>>54005 per book So he can buy 27000/54=<27000/54=5500.0>>500 books A: 500
175B Finetuning: [incorrect] The German Shephend's load cosumption is $5 \times 7 = <077 - 35>>35$ kilograms. The German Shephend's load cosumption is $3 \times 7 \approx <07 + 21>>21$ kilograms. So, having to do consumption of the dogs is $35 + 21 = <<35 + 21 = 56>>56$ kilograms. A: 56	175B Verification: [incorrect] He spent \$27000 / \$500 = <<27000/500=54.0>>54 books per school So he can buy 54 books/school x 3 schools = <<54*3=162>>162 books A: 162
1758 Verification: [correct] The 3 German Shepherd dogs consume 3 x 5 = <<23=15>15 kilograms of food per day. The 2 buildings consume 2 x 3 = <<23=6>>6 kilograms of food per day. The two breeds of dogs consume 15 + 6 = <15+6=21>>21 kilograms of food per day. During a week, they will need 21 x 7 = <<21?7=147>>147 kilograms of food. A: 147	

E Verifier Details

As noted in section 4.2, we train verifiers with a joint objective where the model learns to label a model completion as correct or incorrect, in addition to the original language modeling objective. Architecturally, this means our verifiers are language models, with a small scalar head that outputs predictions on a per-token basis.

We implement this scalar head as a single bias parameter and single gain parameter that operate on the logits outputted by the language model's final unembedding layer. Specifically, the bias and gain shift and scale the logit corresponding to a special token in the vocabulary. As such, the logits for other tokens can continue to represent the language modeling objective, while this special token is reserved for the verifier's predictions.

We can choose to initialize the verifier from the same pretrained language model the generator was finetuned from, or from the generator itself. In our ablations the latter performed slightly better; we suspect this is because better understanding the language distribution that the generator learned should only aid the verifier in scoring samples from that distribution. Unless otherwise explicitly stated, we initialize our verifiers from their corresponding generators in all experiments.

When training verifiers with the joint objective, we use an equal mix of language data and verifier data. Because we sample 100 completions for each original training example to generate the verifier data, using an equal mix means we effectively upsample the original language data by a factor of 100. To form the joint objective, we simply add the verifier loss and language modeling loss unweighted, and define an epoch of this joint objective as having seen each verifier example once. With both objectives, we mask out tokens in the question and only train on tokens in the solutions, as visualized in Figure 12.




Figure 12: Visualization of the joint training objective. We mask out tokens in the question and only consider the loss corresponding to tokens in the solution.

F Verifier Visualization



Figure 13: Five cherry-picked samples generated by a 175B finetuned model and scored by a 175B token-level verifier. A green background color indicates a high verifier score, and a red background color indicates a low one.

One benefit of the token-level verifiers is that these models become immediately interpretable: we can visualize the predicted value for each token and better understand how the verifier makes decisions on judging samples. Above we present a visualization of the predicted values for five different cherry-picked questions and model completions, verified by a 175B token-level verifier that was trained on the full training set.

In the visualization, the background color of the text corresponds to the verifier score for that token, where red is low value (predicted incorrect) and green is high value (predicted correct). The second column of the table summarizes the verifier's prediction, and the third column indicates whether the generated model completion was actually correct or incorrect. Any disagreement between the second and third columns indicates that the verifier made an error.

The first row includes a true positive example, where the verifier correctly classifies the completion as correct. Note that the model is initially unsure about whether the solution is correct and gradually gains certainty as the solution progresses: this is likely a property of the verifier training procedure, where it trains on a large fraction of incorrect model-generated samples.

The second row contains a problem where the solution is correct, but the verifier has rated it as incorrect. This is potentially due to the ambiguity between the "4 times" and the "4 potatoes" in the problem description.

The third row consists of another false negative example. However, unlike the previous example, here the model completion contains some faulty reasoning. As such, even though the final answer in the model completion was correct, the natural language explanation was incorrect, and so the verifier correctly assigned a low score.

In the fourth row we see the verifier score a model completion that starts out correct, but where the verifier gradually becomes less confident in the solution as the solution progresses. After the solution makes a clear mistake (saying that \$64 dollars were spent, instead of the 64 + 16 + 8 = \$88), the verifier judges the solution as incorrect with a high degree of confidence.

The final row contains a false positive, where the model makes a mistake on the second step, where it subtracts 400 from the price of a diamond jewel instead of a gold one. Verifiers occasionally make mistakes with performing this variable binding of quantities to their relationships.